

Base Part Number: 34734G01

**2002
E-Z-GO PERSONNEL CARRIER
4 WHEEL GASOLINE
SHUTTLE 954G**

STANDARD EQUIPMENT: (4 Cycle)

Engine: 11 H.P. rated, 4 cycle, 350 cc twin cylinder, air cooled

Valve train: Overhead valve, overhead cam.

Lubrication: Pressurized oil system, washable permanent filter, wet sump.

Balancer: Internal counter rotating balance shaft.

Ignition: Solid state with crank trigger, electronic timing advance.

Carburetor: Fixed jet float bowl with remote pulse fuel pump.

Air Cleaner: Replaceable dry cartridge.

Electrical System: External starter/generator, 12 volt maintenance free battery, 360 CCA, 51 minute reserve.

Drive Train: Automatic, continuously variable transmission (CVT) forward and reverse.

Transaxle: High efficiency differential with helical gears, 13.32:1 ratio, ground speed governor.

Brakes: Dual rear wheel, hydraulic drum brakes with non-asbestos linings. Hand ratcheted parking brake.

Front Suspension: Multiple leaf springs with hydraulic shock absorbers.

Rear Suspension: Multiple leaf springs with hydraulic shock absorbers.

Steering: Double reduction rack and pinion.

Fuel System: 6.5 gallon tank with instrument panel mounted fuel gauge.

Seating: Two molded one piece construction seats. Seating for five occupants.

Speed: Automatically governed to 15 MPH on level ground (unloaded).

DIMENSIONAL SPECIFICATIONS:

Weight: 1,005 lbs. dry, fuel capacity 40 lbs.

Length: 129 inches

Width: 46.5 inches (at wheels)

Height: 45.5 inches (at steering wheel)

Floor Height: 15.25 inches (front) 11.5 inches (rear)

Ground Clearance: 5 inches (at differential)

Seat Height: 29 inches

Wheel Base: 56.0 inches

Cargo Deck Size: 44.5 W X 37.6 L (47.75 W with racks)

Cargo Deck Height: 26.5 inches (27.8 inches to top of frame)

Turning Clearance Diameter: 22.0 feet

Intersection Aisle Clearance: 84 inches

Tires: 5.70 X 8 (6 ply rated)

Load Capacity: 1,600 lbs. (including operator, passengers, accessories and cargo)

FEATURES:

1. **Seats:** Tilts for access to steering linkage, and drive package.
2. **Chassis:** Welded high yield strength tubular steel.
3. **Body:** Champagne molded fiberglass reinforced plastic.
4. **Body Protection:** Wrap-around bumper and protective side molding.
5. **Safety:** Removable switch key, electric horn, brake lights, handgrip and hip restraints, reverse warning indicator, "deadman" accelerator control, manual F & R switch.
6. **Lighting Package:** Single Light Bar Assembly, taillights, and brake lights.
7. **Steering Wheel:** Molded high impact plastic with dual handgrips, pencil holder, and a convenient clipboard.
8. **Cargo Deck:** Glass filled composite plastic deck hinged for access to drive package and storage area.
9. **Low Oil pressure indicator light**
10. **Analog fuel level gauge**

Base Part Number: 34734G01

PAGE 2

OPTIONS:

Non-Standard Colors
Hydraulic Front Disc Brakes
Turn Signals with 4 Way Flasher
Heavy Duty 12V Battery
USA Trail, Load Range C, 5.70 X 8 Foam Filled
Keyless Ignition System

ACCESSORIES:

Rear Hitch (Pintle or "E")
Muffler Spark Arrester Kit
Weather Protection Package
Hour Meter
Lightweight Canopy (white or champagne)
Windshield
Hub Caps: Silver Spoke
Gold Spoke

Specifications subject to change without notice.