

Base Part Number: 76042

**2002
E-Z-GO WORKHORSE ST350
4 WHEEL GASOLINE**

STANDARD EQUIPMENT:

Engine: 11.0 H.P. rated, 4 cycle, 350 cc twin cylinder, air cooled

Valve Train : Overhead valve, overhead cam.
Lubrication : Pressurized oil system, washable permanent filter
Balancer : Internal counter rotating balance shaft
Ignition : Solid state with crank trigger, electronic timing advance, and RPM limiter.
Carburetor : Fixed jet float bowl with remote pulse fuel pump.
Air Cleaner : Replaceable dry cartridge.
Exhaust : Spark Arrester Muffler Kit

Electrical System : External starter/generator, 12 volt maintenance free battery, 360 CCA, 51 minute reserve
Drive Train : High efficiency differential with helical gears, 13.32:1 ratio, ground speed governor
Transaxle : Automatic, continuously variable transmission (CVT) forward and reverse
Brakes : Dual rear wheel self adjusting mechanical drum brakes, Automatic park brake release with self compensating system
Front Suspension : Leaf springs with hydraulic shock absorbers
Rear Suspension : Leaf springs with hydraulic shock absorbers
Steering : Self-compensating single reduction rack and pinion
Seating : Vacuum formed fabric backed vinyl covers over cushion foam. Standard seating for operator and one passenger.
Fuel System : 6.0 gallon tank with analog fuel gage in instrument panel.
Speed : Factory set to 15 MPH maximum.
Tires : 21x9-10 Work Mate
Additional : Headlights, Brush guard for engine and drive belt, Trailer Hitch w/o Ball

DIMENSIONAL SPECIFICATIONS:

Weight : 974 lbs. Dry (fuel capacity 31 lbs.)
Length : 110.5 inches
Width : 48 inches (at bed)
Height : 49 inches (at steering wheel)
Floor Height : 15 inches
Load Bed Height : 32 inches
Ground Clearance : 6.0 inches (at differential)
Seat Height : 31.75 inches
Wheel Base : 77 inches
Front Wheel Tread : 37.75 inches
Rear Wheel Tread : 38.25 inches
Turning Clearance Dia : Approx 23.5 feet
Load Capacity : 800 lbs. (including operator, passengers, accessories and cargo) *500 lb max cargo bed load.
Load Bed Size : 48" wide, 40" long, 12" deep * 13.3 cubic feet (.49 cubic yards)

FEATURES:

Load Bed : Tilts for complete access to drive package
Electric dump
Removable sides and tailgate
Full Bed and tailgate liner
Chassis : Welded high yield strength tubular steel.
Body : Front : Flexible impact resistant front cowl.
Rear : Steel, replaceable lightweight galvaneal panels.
Finish : Durashield™ powder primer and top coat
Body Protection : Flexible Front Flair and Flexible Rear fenders, tubular steel front bumper with brush guards.

Safety : Keyswitch
Reverse warning indicator
“deadman” accelerator control
Handgrip and hip restraints
Manual F & R switch
Headlights - Halogen
Horn
Skid Plate
Center Console : Instrument panel with four drink holders.
Steering Wheel : Sport Model

O

PTIONS:

Lighting

Light Bar : Beacon and/or Flood Lights
Turn Signals With 4 Way Flasher
Taillights, and Brake Lights
Brake Lights

Instrumentation

Low Fuel Indicator Light
Low Oil Pressure Indicator Light

Weather Enclosures

Cab - Steel
Steel Door Set
Vinyl Door Set
Strobe Light Kit
Dome Light Kit
Work Light Kit
Defroster/Cooling Fan Kit
Electric Heater Kit
Switch Panel and Fuse Kit
Outside Mirror Kit
Sun Canopy Kit - Tan
Windshield Kit (Sun Canopy Required)
Weather Protection Package - Tan or Camouflage

Cargo Bed

Flat Bed
Wood Stake Bed Sides
Tool Box - Heavy Duty Aluminum

Tires / Wheels

Tires: 20" - 10" X 10" Turfer Saver
6" Moon Hub Caps

Misc.

Heavy Duty Battery
Rear View Mirror (Sun Canopy Required)
Winch with Front/Rear Receiver - Remote
Trailer Ball - 1⁷/₈ "
12 Volt power outlet
Right-hand Glove Box - Locking
Rear Receiver Hitch / clevis type
Ash Tray
Hour Meter

Specifications subject to change without notice.