

Base Part Number: 76071

**2002  
E-Z-GO WORKHORSE ST480  
4 WHEEL GASOLINE**

---

**STANDARD EQUIPMENT:**

**Engine:** 16.0 H.P. (11.9 kw) rated, 4 cycle, 480 cc (29.2 ci) twin cylinder, air cooled

**Valve Train :** Overhead valve.  
**Lubrication :** Pressurized oil system, replaceable automotive type filter  
**Carburetor :** Fixed jet float bowl with remote pulse fuel pump.  
**Air Cleaning System:** Replaceable dry cartridge with remote intake.  
**Ignition :** Magnetron™ Ignition with self-contained transistor module.

**Electrical System :** External starter/generator, 12 volt maintenance free battery, 515 CCA, 82 minute reserve  
**Drive Train :** High efficiency differential with helical gears and differential lock, 13.32:1 ratio, ground speed governor  
**Transaxle :** Automatic, continuously variable transmission (CVT) forward and reverse  
**Brakes :** Dual rear wheel self adjusting hydraulic drum brakes. Hand operated parking brake mounted in center console.  
**Front Suspension :** Leaf springs with hydraulic shock absorbers  
**Rear Suspension :** Leaf springs with hydraulic shock absorbers  
**Steering :** Self-compensating single reduction rack and pinion  
**Seating :** Individual bucket seats for operator and one passenger with vacuum formed fabric backed vinyl covers over cushion foam.  
**Fuel Capacity :** 6.0 gallon (3.7L) tank. 31 lbs. (14kg)  
**Speed :** Factory set to 16.5 MPH maximum.  
**Tires :** 22 x 9 – 10 Stryker 1  
**Additional :** Headlights, Brush guard for engine and drive belt, Trailer Hitch w/o Ball, Front and Rear receiver

---

**DIMENSIONAL SPECIFICATIONS:**

**Weight :** 1050 lbs. (476 kg) Dry  
**Length :** 110.5 in. (280.6 cm)  
**Width :** 48 in. (122 cm) at bed  
**Height :** 49 in. (125 cm) at steering wheel  
**Floor Height :** 15 in. (38 cm)  
**Load Bed Height :** 34 in. (86 cm)  
**Ground Clearance :** 6.0 in. (15 cm) at differential  
**Seat Height :** 33 in. (84 cm)  
**Wheel Base :** 77 in. (196 cm)  
**Front Wheel Tread :** 37.75 in. (96 cm)  
**Rear Wheel Tread :** 38.25 in. (97 cm)  
**Turning Clearance Dia :** 23.5 ft. (7.2 m)  
**Load Capacity :** 800 lbs. (363 kgs) including operator, passengers, accessories and cargo, 500 lbs. (227 kgs) max cargo bed load.  
**Load Bed Size:** 48" wide, 40" long, 12" deep, 13.3 cubic feet (.49 cubic yards)

---

**FEATURES:**

**Load Bed :** Tilts for complete access to drive package  
Electric dump  
Removable sides and tailgate  
Full Bed and tailgate liner  
**Chassis :** Welded high yield strength tubular steel.  
**Body :** Front : Flexible impact resistant front cowl.  
Rear : Steel, replaceable lightweight panels.  
**Finish :** Durashield™ primer and top coat  
**Body Protection :** Flexible Front Flare and Flexible Rear fenders, tubular steel front bumper with brush guards.

- **Operation :** Keyswitch  
Reverse warning indicator  
“deadman” accelerator control  
Handgrip and hip restraints  
Headlights – Halogen  
Horn  
Powertrain skid plate
- Instrument Panel :** Includes four drink holders, Analogue fuel gauge, low oil indicator light and 12v power outlet
- Control Console :** Includes manual F & R switch, park brake handle, choke lever and differential lock control
- Steering Wheel :** Sport Model

---

**PTIONS:**

**Lighting**

- Taillights
- Brake Lights

**Weather Enclosures**

- Sun Canopy Kit – Tan
- Windshield Kit, split or one piece, Lexan or Acrylic (Sun Canopy Required)
- Weather Protection Package - Tan or Camouflage

**Cargo Bed**

- Tool Box - Heavy Duty Aluminum

**Tires / Wheels**

- Tires: 20 x 10 – 10 x Turf Saver
- 21 x 9 – 10 Work Mate

**Misc.**

- Ash Tray
- Rear View Mirror (Sun Canopy Required)
- Winch with Front/Rear Receiver - Remote
- Trailer Ball - 1<sup>7</sup>/<sub>8</sub> “
- Locking Glove Box, right and/or left side
- Rear Receiver Hitch / clevis type
- Hour meter

**Non-Standard Colors:** White, Yellow, Champagne, Red, Blue

Specifications subject to change without notice.