

Base Part Number: 76070

**2002  
E-Z-GO WORKHORSE ST SPORT  
PRODUCT SPECIFICATIONS**

---

**STANDARD EQUIPMENT:**

**Engine:** 11.0 H.P. rated, 4 cycle, 350 cc twin cylinder, air cooled

**Valve Train :** Overhead valve, overhead cam.  
**Lubrication :** Pressurized oil system, washable permanent filter  
**Balancer :** Internal counter rotating balance shaft  
**Ignition :** Solid state with crank trigger, electronic timing advance, and RPM limiter.  
**Carburetor :** Fixed jet float bowl with remote pulse fuel pump.  
**Air Cleaner :** Replaceable dry cartridge with remote air intake

**Electrical System :** External starter/generator, 12 volt maintenance free battery, 360 CCA, 51 minute reserve  
**Drive Train :** High efficiency differential with helical gears, 13.32:1 ratio, ground speed governor  
**Transaxle :** Automatic, continuously variable transmission (CVT) forward and reverse  
**Brakes :** Dual rear wheel self adjusting mechanical drum brakes, Automatic park brake release with self compensating system  
**Front Suspension :** Leaf springs with hydraulic shock absorbers  
**Rear Suspension :** Leaf springs with hydraulic shock absorbers  
**Steering :** Self-compensating single reduction rack and pinion  
**Seating :** Vacuum formed fabric backed vinyl covers over cushion foam. Standard seating for operator and one passenger.  
**Fuel System :** 6.0 gallon tank with analog fuel gage in instrument panel.  
**Speed :** Factory set to 15 MPH maximum.  
**Tires :** 21x9-10 Work Mate  
**Additional :** Headlights, Brush guard for engine and drive belt.

---

**DIMENSIONAL SPECIFICATIONS:**

**Weight :** 972 lbs. Dry (441 kgs), fuel capacity 31 lbs (14 kgs)  
**Length :** 103 inches (260 cm)  
**Width :** 46.5 inches (118 cm)  
**Height :** 49 inches (124 cm) at steering wheel  
**Floor Height :** 15 inches (38 cm)  
**Load Bed Height :** 32 inches (81 cm)  
**Ground Clearance :** 6.0 inches (15 cm) at differential  
**Seat Height :** 31.75 inches (81 cm)  
**Wheel Base :** 65.5 inches (166 cm)  
**Front Wheel Tread :** 37.75 inches (96 cm)  
**Rear Wheel Tread :** 38.25 inches (97 cm)  
**Turning Clearance Dia :** 20.3 feet  
**Load Capacity :** 650 lbs. (295 kgs) including operator, passengers, accessories and cargo, 250 lbs. (113 kgs) max cargo bed load.  
**Load Bed Size:** 46 inches wide, 35 inches long, 10 inches deep (117cm x 89 cm x 25 cm)  
9.3 cubic feet (.26 cubic meters)


---

**FEATURES:**

**Load Bed :** Heavy duty bed liner with tailgate cover. Removable tailgate  
**Chassis :** Welded high yield strength tubular steel.  
**Body :** Front : Flexible impact resistant front cowl.  
Rear : Steel, replaceable lightweight galvaneal panels.  
**Finish :** Durashield™ powder primer and top coat  
**Body Protection :** Flexible Front Flair and Flexible Rear fenders, tubular steel front bumper with brush guards.



- Safety :** Keyswitch  
Reverse warning indicator  
“deadman” accelerator control  
Handgrip and hip restraints  
Manual F & R switch  
Headlights – Halogen  
Horn  
Skid Plate
- Center Console :** Instrument panel with four drink holders.
- Steering Wheel :** Sport Model



**PTIONS:**

**Lighting**

- Turn Signals With 4 Way Flasher
- Taillights
- Brake Lights

**Weather Enclosures**

- Sun Canopy Kit - Tan
- Windshield Kit, one piece or split, Acrylic or Polycarbonate (Sun Canopy Required)
- Weather Protection Package - Tan or Camouflage

**Tires / Wheels**

- Tires: 20" - 10" X 10" Turf Saver

**Hitch**

- Ball type – 1<sup>7</sup>/<sub>8</sub>"
- Clevis type
- Bar type

**Misc.**

- Heavy Duty Battery (530 cca @ 0 deg F)
- Ash Tray
- Rear View Mirror (Sun Canopy Required)
- Hour Meter
- 12 Volt power outlet
- Right-hand Glove Box – Locking
- Left-hand Glove Box - Locking
- Rear Receiver Hitch / clevis type
- High Altitude kits
- Individual keyed
- Non standard key switch
- Bed cargo rack – 40"

Specifications subject to change without notice.